acc. to 29 CFR 1910.1200 App D

# **Details Manufacturing Bees Knees**

Version number: GHS 1.0

DMD

#### Date of compilation: 2017-05-10

#### **SECTION 1: Identification**

DETAILS

#### 1.1 Product identifier

Trade name Alternative name(s)

#### **Details Manufacturing Bees Knees**

Top Line VOC, VOC363, Top Line

#### **1.2** Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

#### Vehicle polish

#### 1.3 Details of the supplier of the safety data sheet

MANUFACTURING & DISTRIBUTING

Details Manufacturing & Distributing 504 E Lincoln Way Ames, IA 50010 515.233.6555

Luke.Stagg@detailsmfg.com Josh.Stagg@detailsmfg.com

#### 1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency number

#### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
A.4S	skin sensitization	1	Skin Sens. 1	H317
A.7	reproductive toxicity	2	Repr. 2	H361f
A.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger
- Pictograms

GHS07, GHS08



#### - Hazard statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H361f	Suspected of damaging fertility.

acc. to 29 CFR 1910.1200 App D

**Details Manufacturing Bees Knees** 

#### Version number: GHS 1.0

DMD

Date of compilation: 2017-05-10

Precautionary stateme	ents
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

octamethylcyclotetrasiloxane, Naphtha (petroleum), hydrotreated heavy, CMIT/MIT mixture

#### 2.3 Other hazards

Special danger of slipping by leaking/spilling product.

#### Hazards not otherwise classified

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and chronic).

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not relevant (mixture)

#### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Naphtha (petroleum), hydrotreated heavy	CAS No 64742-48-9	10-<25	Flam. Liq. 3 / H226 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304
Distillates (petroleum), hydro- treated light	CAS No 64742-47-8	1-<5	Flam. Liq. 4 / H227 Acute Tox. 3 / H331 Asp. Tox. 1 / H304
octamethylcyclotetrasiloxane	CAS No 556-67-2	1-<5	Flam. Liq. 3 / H226 Repr. 2 / H361f
Alcohols, C9-11 ethoxylated	CAS No 68439-46-3	1-<5	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Eye Dam. 1 / H318
CMIT/MIT mixture	CAS No 55965-84-9	<1	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1 / H317



acc. to 29 CFR 1910.1200 App D

# **Details Manufacturing Bees Knees**

Version number: GHS 1.0

Date of compilation: 2017-05-10

For full text of abbreviations: see SECTION 16.

#### **SECTION 4: First-aid measures**

#### 4.1 Description of first- aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### **4.2 Most important symptoms and effects, both acute and delayed** Symptoms and effects are not known to date.

# **4.3** Indication of any immediate medical attention and special treatment needed none

#### **SECTION 5: Fire-fighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media Water jet

#### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.



# **Details Manufacturing Bees Knees**

Version number: GHS 1.0

DMC

DETAILS

Date of compilation: 2017-05-10

#### **SECTION 6: Accidental release measures**

MANUFACTURING & DISTRIBUTING

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill Covering of drains

Advices on how to clean up a spill Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

#### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.


#### 7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as Frost

#### 7.3 Specific end use(s)

See section 16 for a general overview.



acc. to 29 CFR 1910.1200 App D

# **Details Manufacturing Bees Knees**

Version number: GHS 1.0

Date of compilation: 2017-05-10

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	ldentifi- er	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Source
US	alpha-alumina	1344-28-1	PEL		15			29 CFR OSHA
US	alpha-alumina	1344-28-1	PEL		5			29 CFR OSHA
US	glycerol	56-81-5	PEL		15			29 CFR OSHA
US	glycerol	56-81-5	PEL		5			29 CFR OSHA
US	petroleum distillates (naph- tha) (rubber solvent)	64742-48-9	PEL	500	2,000			29 CFR OSHA

 $\frac{\text{Notation}}{\text{STEL}}$ 

TWA

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

Relevant DNELs of components of the mixture							
Name of substance	CAS No	End- point	Threshold level	Protection goal, route of exposure	Used in	Exposure time	
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects	
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects	
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local ef- fects	
octamethylcyclotet- rasiloxane	556-67-2	DNEL	73 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local ef- fects	
Alcohols, C9-11 eth- oxylated	68439-46-3	DNEL	2,080 mg/kg	human, dermal	worker (industry)	chronic - systemic effects	
Alcohols, C9-11 eth- oxylated	68439-46-3	DNEL	294 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects	

Relevant PNECs of components of the mixture							
Name of substance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time	
octamethylcyclotet- rasiloxane	556-67-2	PNEC	10 <sup>mg</sup> / <sub>l</sub>	microorganisms	sewage treatment plant (STP)	short-term (single instance)	
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.059 <sup>mg</sup> / <sub>kg</sub>	pelagic organisms	sediment	short-term (single instance)	
octamethylcyclotet- rasiloxane	556-67-2	PNEC	1.7 <sup>mg</sup> / <sub>kg</sub>	(top) predators	water	short-term (single instance)	
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.44 <sup>µg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)	



# **Details Manufacturing Bees Knees**

Version number: GHS 1.0

ſ

DMC

DETAILS

MANUFACTURING & DISTRIBUTING

Date of compilation: 2017-05-10

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.044 <sup>µg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	10 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	3 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sedi- ment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.3 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.59 <sup>mg</sup> / <sub>kg</sub>	benthic organisms	sediment	short-term (single instance)
octamethylcyclotet- rasiloxane	556-67-2	PNEC	0.16 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	0.1038 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	0.1038 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	1.4 <sup>mg</sup> / <sub>l</sub>	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	13.7 <sup>mg</sup> / <sub>kg</sub>	benthic organisms	sediment	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	13.7 <sup>mg</sup> / <sub>kg</sub>	pelagic organisms	sediment	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	1 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)
Alcohols, C9-11 eth- oxylated	68439-46-3	PNEC	0.014 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	water	intermittent re- lease

#### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

#### Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leaktightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

acc. to 29 CFR 1910.1200 App D

## **Details Manufacturing Bees Knees**

Version number: GHS 1.0

DMD

DETAILS

Date of compilation: 2017-05-10

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

MANUFACTURING & DISTRIBUTING

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

#### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid (viscous)
Color	off-white
Odor	fruity

#### Other safety parameters

pH (value)	8-8.6 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 101.3 kPa >212 °F at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.7 vol%
- Upper explosion limit (UEL)	19 vol%
Vapor pressure	3.7 kPa at 37.8 °C
Density	8 lbs/US Gal
Vapor density	this information is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	311 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

# **Details Manufacturing Bees Knees**

Version number: GHS 1.0

#### 9.2 Other information

Temperature class (USA, acc. to NEC 500)

 $T2 \ (\text{maximum permissible surface temperature on the equipment:} \\ \texttt{300°C})$ 

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

### 10.5 Incompatible materials

Oxidizers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

#### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture Name of substance CAS No Exposure route ATE 5.28 mg/l/4h Distillates (petroleum), hydrotreated light 64742-47-8 inhalation: vapor 1,200 <sup>mg</sup>/kg Alcohols, C9-11 ethoxylated 68439-46-3 oral 2,000 <sup>mg</sup>/<sub>kg</sub> Alcohols, C9-11 ethoxylated 68439-46-3 dermal 100 mg/kg CMIT/MIT mixture 55965-84-9 oral 300 <sup>mg</sup>/<sub>kg</sub> CMIT/MIT mixture 55965-84-9 dermal 3 <sup>mg</sup>/<sub>l</sub>/4h CMIT/MIT mixture 55965-84-9 inhalation: vapor

Skin corrosion/irritation

Causes skin irritation.

acc. to 29 CFR 1910.1200 App D

# **Details Manufacturing Bees Knees**

Version number: GHS 1.0

DMD

DETAILS

Date of compilation: 2017-05-10

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Shall not be classified as germ cell mutagenic.

MANUFACTURING & DISTRIBUTING

Carcinogenicity Shall not be classified as carcinogenic.

Reproductive toxicity Suspected of damaging fertility.

Specific target organ toxicity - single exposure Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	5 <sup>mg</sup> / <sub>l</sub>	fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	1.4 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 h
octamethylcyclotet- rasiloxane	556-67-2	LC50	>22 <sup>µg</sup> / <sub>l</sub>	fish	96 h
octamethylcyclotet- rasiloxane	556-67-2	EC50	>1,000 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	96 h
Alcohols, C9-11 eth- oxylated	68439-46-3	LC50	7 <sup>mg</sup> / <sub>l</sub>	fish	96 h
Alcohols, C9-11 eth- oxylated	68439-46-3	EC50	2.5 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EC50	15.41 <sup>mg</sup> / <sub>l</sub>	microorganisms	40 h
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	17 <sup>mg</sup> / <sub>l</sub>	fish	24 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	4.6 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	24 h
octamethylcyclotet- rasiloxane	556-67-2	LC50	10 <sup>µg</sup> / <sub>l</sub>	fish	14 d
octamethylcyclotet- rasiloxane	556-67-2	EC50	>500 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	24 h

# **Details Manufacturing Bees Knees**

Version number: GHS 1.0

DMC

Date of compilation: 2017-05-10

# **12.2 Persistence and degradability** Data are not available.

MANUFACTURING & DISTRIBUTING

- **12.3 Bioaccumulative potential** Data are not available.
- **12.4 Mobility in soil** Data are not available.

DETAILS

- **12.5 Results of PBT and vPvB assessment** Data are not available.
- **12.6** Other adverse effects Data are not available.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Sewage disposal-relevant information Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

List of wastes

Not assigned

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SEC	TION 14: Transport information	
14.1	UN number	not subject to transport regulations
14.2	UN proper shipping name	not relevant
14.3	Transport hazard class(es)	
	Class	-
14.4	Packing group	not relevant
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6	Special precautions for user There is no additional information.	

#### **14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code** The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) Not subject to transport regulations.

acc. to 29 CFR 1910.1200 App D

## **Details Manufacturing Bees Knees**

Version number: GHS 1.0

DMC

DETAILS

Date of compilation: 2017-05-10

#### International Maritime Dangerous Goods Code (IMDG) Not subject to IMDG.

MANUFACTURING & DISTRIBUTING

# International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

### **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

#### SARA TITLE III (Superfund Amendment and Reauthorization Act)

- List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304) none of the ingredients are listed

#### CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

- Section 102(A) Hazardous Substances (40 CFR 302.4) none of the ingredients are listed

Clean Air Act none of the ingredients are listed

# California Environmental Protection Agency (Cal/EPA): Proposition 65 Chemicals known to the State to cause cancer or reproductive toxicity

none of the ingredients are listed

#### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	1	material that is normally stable but can become unstable (self-react) at high temperatures and pressures. Material may react non-violently with water or undergo hazardous polymer- ization in the absence of inhibitors
Personal protective equipment	-	

#### **NFPA® 704**

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

acc. to 29 CFR 1910.1200 App D

# **Details Manufacturing Bees Knees**

Version number: GHS 1.0

Date of compilation: 2017-05-10

#### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### SECTION 16: Other information, including date of preparation or last revision

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR OSHA	29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative



**Details Manufacturing Bees Knees** 

Version number: GHS 1.0

DMC

DETAILS

Date of compilation: 2017-05-10

#### Key literature references and sources for data

MANUFACTURING & DISTRIBUTING

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### **Classification procedure**

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.