

## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name

Details Manufacturing Premium Spray Wax Concentrate

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Vehicle spray wax

#### 1.3 Details of the supplier of the safety data sheet

Details Manufacturing & Distributing  
504 E Lincoln Way Ames, IA 50010  
515.233.6555

Luke.Stagg@detailsmfg.com Josh.Stagg@detailsmfg.com

#### 1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500  
24 hour emergency number

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
B.6	flammable liquid	3	Flam. Liq. 3	H226
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS07,  
GHS08

- Hazard statements

H226 Flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P264 Wash thoroughly after handling.  
P280 Wear protective gloves/eye protection/face protection.



## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

### - Precautionary statements

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P321 Specific treatment (see on this label).
- P331 Do NOT induce vomiting.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling naphthenic oil, severely hydrotreated

### 2.3 Other hazards

Hazards not otherwise classified

- May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).
- Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and chronic).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
naphthenic oil, severely hydrotreated	CAS No 64741-86-2	10 - < 25	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Asp. Tox. 1 / H304
2-butoxy-1-ethanol	CAS No 111-76-2	1 - < 5	Flam. Liq. 4 / H227 Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2A / H319
Propan-2-ol	CAS No 67-63-0	1 - < 5	Flam. Liq. 2 / H225 Eye Irrit. 2A / H319 STOT SE 3 / H336

For full text of abbreviations: see SECTION 16.

## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

### SECTION 4: First-aid measures

#### 4.1 Description of first- aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

##### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

##### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO<sub>2</sub>)

##### Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

##### Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10.

Disposal considerations: see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

### - Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

### Control of the effects

Protect against external exposure, such as

Frost

### - Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

### - Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

## 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Source
US	2-butoxyethanol	111-76-2	PEL	50	240			29 CFR OSHA
US	isopropyl alcohol	67-63-0	PEL	400	980			29 CFR OSHA

#### Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2-butoxy-1-ethanol	111-76-2	DNEL	75 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
2-butoxy-1-ethanol	111-76-2	DNEL	98 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Propan-2-ol	67-63-0	DNEL	888 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Propan-2-ol	67-63-0	DNEL	500 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2-butoxy-1-ethanol	111-76-2	PNEC	8.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	0.88 mg/l	aquatic organisms	marine water	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	463 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)

## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2-butoxy-1-ethanol	111-76-2	PNEC	34.6 mg/kg	benthic organisms	sediment	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	3.13 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-butoxy-1-ethanol	111-76-2	PNEC	9.1 mg/l	aquatic organisms	water	intermittent re-release
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	marine water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	2,251 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 mg/kg	benthic organisms	sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 mg/kg	pelagic organisms	sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	160 mg/kg	(top) predators	water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	28 mg/kg	terrestrial organisms	soil	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	water	intermittent re-release

### 8.2 Exposure controls

#### Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment)

##### Eye/face protection

Wear eye/face protection.

##### Skin protection

###### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

###### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.



## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

Physical state	liquid
Color	green
Odor	characteristic

#### Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	82.5 °C
Flash point	57 °C at 101.3 kPa 135 °F at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)
Explosive limits	not determined
Vapor pressure	4.3 kPa at 20 °C
Density	0.96 g/cm <sup>3</sup>
Vapor density	this information is not available

#### Solubility(ies)

- Water solubility	miscible in any proportion
--------------------	----------------------------

#### Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

Auto-ignition temperature	225 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2D (maximum permissible surface temperature on the equipment: 215°C)
--	---

**SECTION 10: Stability and reactivity**

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

**SECTION 11: Toxicological information**

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
naphthenic oil, severely hydrotreated	64741-86-2	inhalation: vapor	11 mg/√4h
naphthenic oil, severely hydrotreated	64741-86-2	inhalation: dust/mist	4.6 mg/√4h
2-butoxy-1-ethanol	111-76-2	oral	1,746 mg/kg
2-butoxy-1-ethanol	111-76-2	dermal	1,100 mg/kg
2-butoxy-1-ethanol	111-76-2	inhalation: vapor	11 mg/√4h





Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
2-butoxy-1-ethanol	111-76-2	3	Volume 88
Propan-2-ol	67-63-0	3	Volume 15, Sup 7, 71

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
napthenic oil, severely hydrotreated	64741-86-2	LL50	1.13 mg/l	fish	96 h
napthenic oil, severely hydrotreated	64741-86-2	EL50	7.385 mg/l	aquatic invertebrates	48 h
2-butoxy-1-ethanol	111-76-2	LC50	1,474 mg/l	fish	96 h
2-butoxy-1-ethanol	111-76-2	EC50	1,550 mg/l	aquatic invertebrates	48 h
2-butoxy-1-ethanol	111-76-2	ErC50	1,840 mg/l	algae	72 h
Propan-2-ol	67-63-0	LC50	10,000 mg/l	fish	96 h

## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
naphthenic oil, severely hydrotreated	64741-86-2	LL50	>100 mg/l	fish	24 h
naphthenic oil, severely hydrotreated	64741-86-2	EL50	>1,000 mg/l	aquatic invertebrates	24 h
2-butoxy-1-ethanol	111-76-2	EC50	297 mg/l	aquatic invertebrates	21 d
Propan-2-ol	67-63-0	LC50	>10,000 mg/l	aquatic invertebrates	24 h

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Relevant provisions relating to waste

List of wastes

Not assigned

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

### SECTION 14: Transport information

<b>14.1 UN number</b>	1993
<b>14.2 UN proper shipping name</b>	Combustible liquid, n.o.s.
<b>14.3 Transport hazard class(es)</b>	
Class	3 (flammable liquids)
<b>14.4 Packing group</b>	III (substance presenting low danger)
<b>14.5 Environmental hazards</b>	non-environmentally hazardous acc. to the dangerous goods regulations
<b>14.6 Special precautions for user</b>	
	There is no additional information.
<b>14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code</b>	
	The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number	1993
Proper shipping name	Combustible liquid, n.o.s.
Class	3
Packing group	III
Special provisions (SP)	IB3, T1, T4, TP1

#### **International Maritime Dangerous Goods Code (IMDG)**

UN number	1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	223, 274, 955
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, <u>S-E</u>
Stowage category	A

#### **International Civil Aviation Organization (ICAO-IATA/DGR)**

UN number	1993
Proper shipping name	Flammable liquid, n.o.s.
Class	3
Packing group	III
Danger label(s)	3

## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10



Special provisions (SP)	A3, 274
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

##### SARA TITLE III (Superfund Amendment and Reauthorization Act)

- List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304)  
none of the ingredients are listed
- Specific Toxic Chemical Listings (40 CFR 372) (EPCRA Section 313)  
none of the ingredients are listed

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name acc. to inventory	CAS No	Remarks	Effective date
isopropyl alcohol	67-63-0	Only persons who manufacture by the strong acid process are subject, no supplier notification.	1986-12-31

New Jersey Worker and Community Right to Know Act N.J.S.A. 34:5A-1 et. seq.

Right to Know Hazardous Substance List			
Name acc. to inventory	CAS No	Remarks	Classifications
2-BUTOXY ETHANOL (ETHANOL, 2-BUTOXY-, BUTYL CELLOSOLVE)	111-76-2		CA F2
isopropyl alcohol	67-63-0		F3

##### Legend

- CA Carcinogenic
- F2 Flammable - Second Degree
- F3 Flammable - Third Degree

##### California Environmental Protection Agency (Cal/EPA): Proposition 65 Chemicals known to the State to cause cancer or reproductive toxicity

none of the ingredients are listed

##### Industry or sector specific available guidance(s)

##### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	1	material that is normally stable but can become unstable (self-react) at high temperatures and pressures. Material may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors

## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

Category	Rating	Description
Personal protective equipment	-	

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR OSHA	29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)



## Details Manufacturing Premium Spray Wax Concentrate

Version number: GHS 1.0

Date of compilation: 2017-05-10

Abbr.	Descriptions of used abbreviations
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.