

Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

SECTION 1: Identification

1.1 Product identifier

Trade name **Details Manufacturing Step One**
Alternative name(s) Stage 1 VOC

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Vehicle polishing compound

1.3 Details of the supplier of the safety data sheet

Details Manufacturing & Distributing
504 E Lincoln Way Ames, IA 50010
515.233.6555

Luke.Stagg@detailsmfg.com Josh.Stagg@detailsmfg.com

1.4 Emergency telephone number

Emergency information service USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.7	reproductive toxicity	2	Repr. 2	H361f
A.10	aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS08



- Hazard statements

H304 May be fatal if swallowed and enters airways.
H361f Suspected of damaging fertility.

- Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling octamethylcyclotetrasiloxane, Distillates (petroleum), hydrotreated light

Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Hazards not otherwise classified

Contains CMIT/MIT mixture. May produce an allergic reaction.

May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).

Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and chronic).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
Distillates (petroleum), hydro-treated light	CAS No 64742-47-8	10 - < 25	Flam. Liq. 4 / H227 Acute Tox. 3 / H331 Asp. Tox. 1 / H304
octamethylcyclotetrasiloxane	CAS No 556-67-2	1 - < 5	Flam. Liq. 3 / H226 Repr. 2 / H361f
odorless mineral spirits	CAS No 64742-48-9	1 - < 5	Flam. Liq. 3 / H226 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304
decamethylcyclopentasiloxane	CAS No 541-02-6	1 - < 5	Flam. Liq. 4 / H227
CMIT/MIT mixture	CAS No 55965-84-9	< 1	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Skin Sens. 1 / H317

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: Sawdust, Kieselgur (diatomite), Sand, Universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal precautions: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation
Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingsuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as
Frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)								
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Source
US	alpha-alumina	1344-28-1	PEL		15			29 CFR OSHA
US	alpha-alumina	1344-28-1	PEL		5			29 CFR OSHA
US	glycerol	56-81-5	PEL		15			29 CFR OSHA
US	glycerol	56-81-5	PEL		5			29 CFR OSHA
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000			29 CFR OSHA

Notation

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period unless otherwise specified

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24.2 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97.3 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.059 mg/kg	pelagic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	1.7 mg/kg	(top) predators	water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.44 µg/l	aquatic organisms	freshwater	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.044 µg/l	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.3 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.59 mg/kg	benthic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.16 mg/kg	terrestrial organisms	soil	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	benthic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	13 mg/kg	(top) predators	water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	3.77 mg/kg	terrestrial organisms	soil	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	pelagic organisms	sediment	short-term (single instance)



Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (viscous)
Color	pale blue
Odor	characteristic

Other safety parameters

pH (value)	7 – 7.2 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 101.3 kPa >212 °F at 1 atm
Evaporation rate	not determined
Flammability (solid, gas)	not relevant (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.7 vol%
- Upper explosion limit (UEL)	19 vol%

Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

Vapor pressure	3.7 kPa at 37.8 °C
Density	1.082 – 1.101 g/ml
Vapor density	this information is not available
Relative density	1.08 at 25 °C (water = 1)
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	343 °C
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment: 300 °C)
--	---

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)**Acute toxicity**

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Distillates (petroleum), hydrotreated light	64742-47-8	inhalation: vapor	5.28 mg _i /4h
CMIT/MIT mixture	55965-84-9	oral	100 mg _i /kg
CMIT/MIT mixture	55965-84-9	dermal	300 mg _i /kg
CMIT/MIT mixture	55965-84-9	inhalation: vapor	3 mg _i /4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	5 mg/l	fish	96 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	1.4 mg/l	aquatic invertebrates	48 h
octamethylcyclotetrasiloxane	556-67-2	LC50	>22 µg/l	fish	96 h
octamethylcyclotetrasiloxane	556-67-2	EC50	>1,000 mg/l	aquatic invertebrates	96 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	96 h
decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Distillates (petroleum), hydrotreated light	64742-47-8	LL50	17 mg/l	fish	24 h
Distillates (petroleum), hydrotreated light	64742-47-8	EL50	4.6 mg/l	aquatic invertebrates	24 h
octamethylcyclotetrasiloxane	556-67-2	LC50	10 µg/l	fish	14 d
octamethylcyclotetrasiloxane	556-67-2	EC50	>500 mg/l	aquatic invertebrates	24 h
odorless mineral spirits	64742-48-9	EC50	15.41 mg/l	microorganisms	40 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	14 d
decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

List of wastes

Not assigned

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	not subject to transport regulations
14.2	UN proper shipping name	not relevant
14.3	Transport hazard class(es)	
	Class	-
14.4	Packing group	not relevant
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6	Special precautions for user	
	There is no additional information.	
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.



Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

SARA TITLE III (Superfund Amendment and Reauthorization Act)

- List of Extremely Hazardous Substances (40 CFR 355) (EPCRA Section 302 and 304)
none of the ingredients are listed

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

- Section 102(A) Hazardous Substances (40 CFR 302.4)
none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

California Environmental Protection Agency (Cal/EPA): Proposition 65 Chemicals known to the State to cause cancer or reproductive toxicity

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	1	material that is normally stable but can become unstable (self-react) at high temperatures and pressures. Material may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors
Personal protective equipment	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision**Indication of changes (revised safety data sheet)**

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
3.2		Description of the mixture: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR OSHA	29 CFR §1910.1001 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization



Details Manufacturing Step One

Version number: GHS 2.0
Replaces version of: 2017-05-10 (GHS 1)

Revision: 2017-05-10

Abbr.	Descriptions of used abbreviations
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.